
# **DIBROMOMETHANE**



#### 1. PERFORMANCE

1) Measuring range : 2.5-40 ppm Number of pump strokes : 1(100mL)

2) Sampling time : 1.5 minutes/1 pump stroke

3) Detectable limit : -

4) Shelf life : 3 years (Necessary to store in a refrigerated place;  $0\sim10^{\circ}$ C)

5) Operating temperature :  $15 \sim 25^{\circ}$ C

6) Reading : The printed scales are calibrated by Methy bromide at 1 pump stroke.

Dibromomethane concentration is determined by using a conversion chart

at 1 pump stroke

7) Colour change : White  $\rightarrow$  Yellow

### 2. CHEMICAL REACTION

By decomposing with an Oxidizer, Bromine is produced. It reacts with o-Toluidine and yellow Orthoquinone is produced.

## 3. CALIBRATION OF THE TUBE

**GAS CHROMATOGRAPHY** 

### 4. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	ppm	Coexistence
Halogens	Similar stain is produced.		Higher readings are given.
Halogenated hydrocarbons	п		11
Hexane	The accuracy of readings is not affected.	200	Lower readings are given.

### Dibromomethane concentration (ppm)

