
TETRAHYDROTHIOPHENE



Tetrahydrothiophene concentration(ppm)



No. 190U tube reading (ppm)

1. PERFORMANCE

1) Measuring range : 4-100 ppm Number of pump strokes : 3(300mL)

2) Sampling time : 1.5 minutes / 1 pump stroke

3) Detectable limit :

4) Shelf life ∴ 2 years 5) Operating temperature ∴ 15~25°C

6) Reading : The tube scales are calibrated based on Ethyl cellosolve at 3 pump strokes and

Tetrahydrothiophene concentration is determined by using a conversion chart

at 3 pump strokes

7) Colour change : Yellow→Pale blue

2. RELATIVE STANDARD DEVIATION

RSD-low: - RSD-mid.: - RSD-high: -

3. CHEMICAL REACTION

Chromium oxide is reduced. $C_4H_8S + C_7C^6 + H_2SO_4 \rightarrow C_7C^3 + C_7C^3$

4. CALIBRATION OF THE TUBE

GAS CHROMATOGRAPHY

5. INTERFERENCE AND CROSS SENSITIVITY

Substance	Interference	Coexistence
Alcohols	Similar stain is produced.	Higher readings are given.
Ethers	"	"
Aliphatic hydrocarbons (more than C ₃)	Whole reagent is changed to brown.	"
Aromatic hydrocarbons	"	"
Esters	"	"
Ketones	"	"
Halogenated hydrocarbons	"	"