

Air Release Value Apparatus 15840-0

Air Release Properties of Lubricating and Hydraulic Products

ASTM D3427; IP 313; BS 2000 Part 313; ISO 9120; DIN 51 381; NFT 60-149

- Integrated solution
- Multi-station sample handling
- Touch screen display
- Simple test menu
- Automated density monitoring
- Circulated sample heating
- Quick connectors for easy handling
- Integral sinker warmer
- Automatic result calculation
- Memory for 10,000 tests results
- Full LIMS connectivity
- CE marked
- Automated Calibration procedure



Hydraulic Fluids • Lubricating Oils

Seta Air Release Value Apparatus

Air Release Properties of Lubricating and Hydraulic Products

ASTM D3427; IP 313; BS 2000 Part 313; ISO 9120; DIN 51 381; NFT 60-149

Air Release Value

The NEW Seta Apparatus is designed to determine the air release properties of hydrocarbon based oils in accordance with ASTM, IP and other methods. The apparatus is a benchtop instrument with integrated density balance, heater, temperature control system, sinker warmer, pressure regulation and microprocessor based control system, A unique slider arrangement allows easy positioning of the test vessel throughout the test cycle.


Typical Applications

Lubricant and Oils containing excess amounts of entrained air can lead to serious disruptions of equipment in operation, increased oxidation tendency and shortened lubricating efficiency. The ARV (Air Release Value) test determines the time taken for hydraulic fluids and lubricating oils to release entrained air and gases.


Test Method

The sample is heated and subjected to airflow at a specified rate, the duration needed for entrained air to reduce in volume is recorded as the air bubble separation time.


Operator Interface




Quickly and easily start test



Complete test preparation



Follow simple test method guide



View results with key parameters highlighted and a graphical representation



For more information please visit: www.stanhope-seta.co.uk

Seta Air Release Value Apparatus

Air Release Properties of Lubricating and Hydraulic Products

ASTM D3427; IP 313; BS 2000 Part 313; ISO 9120; DIN 51 381; NFT 60-149




Operator Safety

- No need to handle hot sample vessel
- Exhaust filter system extracts oil vapours
- Control interlock prevents heating when there's no air flow
- Safety cut-out prevents overheating
- Protective safety shield around vessel during aeration

Ease Of Use

- Removes traditional operator problems
- Dropping the balance sinker into the hot sample - no longer a concern, the sinker remains permanently fixed to the balance and is either immersed in the sample by raising the test vessel platform or warmed in an integral air bath
- Transferring from aeration to density measurement - a sliding, raising and lowering platform allows the sample to be quickly and precisely moved between the test modes without delay or risk to the operator




Enhanced Test Throughput

- Automated test sequence optimises time taken for each stage of the test
- Less reliance on an operator to maintain the various controls for airflow, temperature and density
- Quick-connectors on glass vessels minimise assembly and cleaning time
- Allows preheated samples to be tested in rapid succession
- Automatic Calibration procedure



Precision and Accuracy

- Automatic timing, temperature control, regulated aeration and integrated density measurement ensures test repeatability



For more information please visit: www.stanhope-seta.co.uk

Seta Air Release Value Apparatus

Air Release Properties of Lubricating and Hydraulic Products

ASTM D3427; IP 313; BS 2000 Part 313; ISO 9120; DIN 51 381; NFT 60-149

Technical Specifications

Seta Air Release Value Apparatus 15840-0	
Air supply	Compressed air or external pump requires 75 kPa and 40 l/min
Sample size	200 ml
Test temperature range	Ambient to 75°C (air to 85°C)
Set temperatures	25°C 50°C 75°C (custom temperature available in software)
Sample temperature stability	±0.1°C
Air temperature stability	±0.2°C
Water supply	10 l/min, adjustable from 25°C to 80°C
Density	0.0001 g/ml (0.1 kg/m ³)
Voltage	100 to 240 AC (switched) 50/60Hz
Current (MAX)	3.5A
Display	Widescreen 7" TFT LCD 800 x 480 resolution
Connectivity	USB type A - test results can be saved to memory stick Ethernet RJ45 for connection to LIMS Printer - Ethernet
Size (H x W x D)	82 x 44 x 50 cm
Weight	29 kg

Minimal Servicing



Weekly:

- Check the accuracy of the balance once a week



Monthly:

- Check temperature calibration monthly

Required Accessories

Part Number		Description
15870-5		Circulating water bath, for test vessel and sinker warmer Stainless steel compact thermostatic bath with built-in stirrer and pump to enable use as a circulator for external apparatus
20290-4		Air pump, for aeration Oil free rotating vane (non-pulsating) for air and non-corrosive gases

Optional Accessories

Part Number		Description
99200-3		Laboratory drying oven A digitally controlled oven suitable for heat storage, heat treatment and drying processes at temperatures up to 300°C for timed periods up to 999 hours
82012-0		Precision plus digital thermometer Range -199 to +199°C. Resolution 0.01°C. 5 point UKAS calibration at 30, 37.8, 55, 90 and 150°C

For more information please visit: www.stanhope-seta.co.uk